

TYPE APPROVAL CERTIFICATE

Certificate No: TAE000033K Revision No: 2

This is to certify:	
That the Bulkhead/Deck Penetration	
with type designation(s) RGPH-50, RGPH-70, RGPH-100, RGPH-125, RGPH-150, RGPH-	-200
MCT Brattberg AB Karlskrona, Sweden	
is found to comply with DNV rules for classification – Ships, offshore units, and high	n speed and light craft
Application:	
Products approved by this certificate are accepted for installa	tion on all vessels classed by DNV.
Issued at Høvik on 2023-01-04	for DNV
This Certificate is valid until 2027-12-31 . DNV local unit: Sweden CMC	
Approval Engineer: Nicolay Horn	Frederik Tore Elter Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Form code: TA 251

Revision: 2022-09

www.dnv.com

Page 1 of 2



Form code: TA 251 Revision: 2022-09 www.dnv.com Page 1 of 2

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-008924-5** Certificate No: **TAE000033K**

Revision No: 2

Product description

RGPH-50 single cable transit up to RGPH-200 multi cable transit.

Application/Limitation

Approved for cable / pipe penetration in bulkheads or decks limited to a pressure of 66.7 bar water tightness.

The penetration system is generally not to be used for penetrating boundaries of tanks, but an approval may be given on a case-by-case basis for penetration of boundaries of tanks limited to a pressure of 40 bar.

Type Approval documentation

Test report QR-314, dated 2006-03-08

Drawings:

- 610093	Rev. B, dated 2005-10-12, RGPH-200 ANSI Flange
- 610096	Rev. B, dated 2005-10-12, RGPH-200
- 6060011	Rev. A, dated 2006-01-04, RGPH-50
- 6140136	Rev. A, dated 2014-04-01, RGPH-70
- 6140138	Rev. A, dated 2014-04-01, RGPH-100
- 6140170	Rev. A, dated 2014-04-15, RGPH-125
- 6140140	Rev. A, dated 2014-04-01, RGPH-150

Tests carried out

Pressure test with water according to DNV class programme DNV-CP-0165 (September 2021).

Marking of product

The product or packagings are to be marked with name of manufacturer and type designation.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 251 Revision: 2022-09 www.dnv.com Page 2 of 2